

Save



# NEO SERIES<sup>®</sup> 4000



Whether your data storage challenges involve rapidly expanding data, complex networking environments, costly downtime or overburdened IT resources, NEO SERIES<sup>™</sup> 4000 midrange libraries deliver the power and performance you need to protect your data center.

## Protect Your Data

No matter how large your data center is or how fast it's growing, NEO SERIES 4000 libraries provide a powerful combination of capacity and speed to ensure that your data center is reliably protected. The NEO 4100 (the smallest model of the NEO SERIES 4000) packs up to 48 TB\* capacity and over 2.3 TB/hr.\* of performance in just 10u of rack space. The NEO 4200 (our largest model) fills a rack with over 96 TB\* of capacity and more than 4 TB/hr.\* of performance—giving you the flexibility to meet a variety of data storage needs.

## Protect Your Investment

NEO 4000 libraries also scale to meet your future data protection needs. As your data expands, NEO 4000 libraries expand with it. Simply add 52-slot or 60-slot modules to your existing NEO 4000 model to instantly and affordably increase your capacity and performance by up to 4 times, while protecting your original library investment. Upgrade to higher performance, next-generation tape drive technologies by simply sliding out existing tape drives and replacing them with higher performance tape drives.

## Maximize Use of Valuable Resources

NEO 4000 libraries maximize the use of your resources by affordably, quickly and reliably backing up and archiving your mission-critical data. Features such as WebTLC<sup>™</sup>, which allows authorized personnel to remotely manage the NEO 4000 library from anywhere in the world, make the NEO 4000 easy to use and operate. NEO's LPO<sup>™</sup> (Library Partitioning Option) lets you partition the library into several smaller libraries, providing multi-server access and allowing you to allocate the cost of the library across the entire data center. Components such as tape drives, power supplies, controllers and interface cards are easily removed, reducing support and service costs.

## Minimize Costly Downtime

NEO's rock-solid, field-proven architecture delivers superior reliability, availability and manageability, eliminating costly downtime in your data center. Features such as NEO's LiveSwap<sup>™</sup> tape drives and removable, redundant power supplies allow removal/replacement without interrupting the SCSI bus and/or power source, assuring that you have

nonstop access to your data. In multi-module environments, NEO's remote fail-over capability lets you transfer control from one module to another, ensuring uninterrupted access to your data.

## Accommodate Complex Networking Environments

The NEO 4000 can easily protect data on your network, whether you are running a single NT server, multiple local servers running UNIX or a worldwide SAN with a complex combination of servers, operating systems and interfaces. Available with either LVD SCSI or Native Fibre Channel interfaces, NEO 4000 provides connectivity choices designed to take advantage of your network performance. Since network architectures change as your operation grows, NEO 4000 provides a V.I.A.<sup>™</sup> (Virtual Interface Architecture) option that also provides you with flexibility to connect to the NEO library via iSCSI or NDMP.

## Compatibility To Keep You Connected

NEO 4000 libraries are supported on all major operating systems including HP-UX, IBM AIX, Linux Mac OS, Novell NetWare, SCO UNIX, Sun Solaris, Tru64 UNIX, Windows NT/2000 and more. For the most current information on compatibility, visit our website at [www.overlandstorage.com](http://www.overlandstorage.com).

## Service You Can Count On

NEO 4000 libraries deliver a 1-year on-site maintenance warranty and are supported by a 2nd and 3rd year XchangeNOW<sup>™</sup> program on all field replaceable components. Additional on-site service options are available in most areas.

## Experience You Can Trust

With 25 years of experience in data protection solutions, and expertise in both disk and tape technologies, Overland meets the needs of IT professionals worldwide by delivering D2D and D2D2T solutions that optimize the data backup, recovery and archive process. With award-winning designs, patented technologies, superior reliability, first-class sales and support, and a variety of solutions to meet a number of different needs, Overland Storage is the right choice for your data protection needs.

- Up to 48 TB capacity
- Up to 2.3 TB/hour performance
- Expansion on demand
- LVD SCSI or Native Fibre Channel interface
- 52-60 cartridges; 1-4 tape drives
- LTO or SDLT



**Overland**  
STORAGE<sup>®</sup>  
Simply Protected

# NEO SERIES® 4000 Specifications

	NEO 4100				NEO 4200			
<b>DRIVES AND MEDIA</b>								
Drive type	LTO-3	LTO-2	SDLT 600	SDLT 320	LTO-3	LTO-2	SDLT 600	SDLT 320
Media type	Ultr 3	Ultr 2	Super DLTape II	Super DLTape I	Ultr 3	Ultr 2	Super DLTape II	Super DLTape I
<b>LIBRARY CONFIGURATION</b>								
Number of cartridges	60	60	52	52	120	120	104	104
Magazines	4	4	4	4	8	8	8	8
Slots per magazine	15	15	13	13	15	15	13	13
Number of drives	1-4	1-4	1-4	1-4	2-8	2-8	2-8	2-8
Mail slots	1	1	1	1	2	2	2	2
<b>CAPACITY</b>								
Native capacity TB	24	12.0	15.6	8.3	48	24.0	31.2	16.6
Compressed capacity* TB	48	24	31.2	16.6	96	48.0	62.4	33.3
<b>PERFORMANCE</b>								
Native transfer (GB/hr.)	288	108	129.6	57.6	576	216	259.2	115.2
w/min. number of drives								
Native transfer (GB/hr.)	1.2 TB/hr.	432	518.4	230.4	2.3 TB/hr.	864	1.1 TB/hr.	460.8
w/max. number of drives								
Compressed transfer (GB/hr.)	576	216	259.2	115.2	1.2 TB/hr.	432	518.4	230.4
w/min. number of drives								
Compressed transfer (GB/hr.)	2.3 TB/hr.	864	1.1 TB/hr.	460.8	4.6 TB/hr.	1.7 TB/hr.	2.1 TB/hr.	921.6
w/max number of drives								
<b>PHYSICAL DIMENSIONS</b>								
Rack mount (HxWxD)	17.5 x 16.7 x 31.9 inches (44.4 x 42.4 x 81 cm)				35.0 x 16.7 x 31.9 inches (88.9 x 42.4 x 81 cm)			
Weight	171 lb. (78 kg.)				342 lb. (155 kg.)			
<b>INTERFACE</b>								
Type of Interface	LVD SCSI or Native FC		LVD SCSI		LVD SCSI or Native FC		LVD SCSI	

\* Assumes compression ratio of 2:1. Actual performance may vary with the application.

With NEO, you can buy based on your current needs and grow as your storage needs grow.



NEO 4100



NEO 4200



NEO 4000 with  
add-on modules



NEO 4000 with  
add-on modules

## WORLDWIDE HEADQUARTERS

4820 Overland Avenue  
San Diego, CA 92123 USA  
**Tel** 1-800-729-8725  
1-858-571-5555  
**Fax** 1-858-571-3664  
**Email** sales@overlandstorage.com

## UNITED KINGDOM (EMEA OFFICE)

Overland House  
Ashville Way  
Wokingham, Berkshire  
RG41 2PL England  
**Tel** +44 (0) 118-9898000  
**Fax** +44 (0) 118-9891897  
**Email** europe@overlandstorage.com

## FRANCE OFFICE

Overland Storage  
13 rue Camille Desmoulins  
92441 Issy les Moulineaux Cedex  
France  
**Tel** +33 (0) 1 58042550  
**Fax** +33 (0) 1 58042636  
**Email** europe@overlandstorage.com

## GERMANY OFFICE

Humboldtstr. 12  
85609 Dornach Germany  
**Tel** +49-89-94490-214  
**Fax** +49-89-94490-414  
**Email** europe@overlandstorage.com

## ASIA PACIFIC OFFICE

Overland Storage  
Level 44, Suntec Tower Three  
8 Temasek Boulevard  
Singapore 038988  
**Tel** +65 6866-3848  
**Fax** +65 6866-3838  
**Email** asia@overlandstorage.com



www.overlandstorage.com

© 2006 Overland Storage. All features, hardware and software performance specifications are subject to change without notice. Overland Storage and all Overland Storage products are trademarks of Overland Storage. All other brands, product names, company names, trade names, trademarks and service marks used are the property of their respective owners. N40-DS0206-03